□ DCS pro Specifications

Fucntions	FULL-HD Live Image (16:9) Comparison image USB2.0 PC Slave Mode Image Adgustment - Brightness,Sharpness,Contrast,Gamma,Exposure - Image Conversion - Selectable color mode(User 1/2/3/Default) - Storaged Image File Play - Create Folder, Delete Folder & File - System Time setting	
Camera Resolution	1920x1080	
Video Out	1920x1080i, 60 frame, HDMI	
PC Interface	USB 2.0 / Slave Mode Directly connected to the PC application	
Internl Storage	32G	
Enternal Storage interface	USB 2.0 Memory Stic /FAT32	
Still image Capture	920x1080 jpg File	
User Key Interface	5 Directional Key	
Light Source	18W LED lamp, Color temperature (4800 $^{\circ}$ K), Adjustable light intensity	
Cable Length	2.0M	
Foot switch	for Freeze & Still Capture	
AC Input	90~264VAC Max 45Watt Universal AC Input / Full range	
Dimension	Width(209mm) x Depth(101mm) x Height(250mm)	

MEDICAL CAMERA SYSTEM



□ Moving Camera Stand Optional

- Hole the camera for still image
- Maintaining focus
- Angle control lever

SOMETECH SINCE 1989

O O O

• Easy moving



SOMETECH INC.

(Ace High-end Tower ||, Guro-dong) 1201ho, 1204ho, 61, Digital-ro 26gil, Guro-gu, Seoul, Korea TEL: +82-2-2025-1000(Rep.) FAX: +82-2-2025-1009 E-mail: overseas@sometech.com / www.sometech.com







CE

Main features

• Optimal solution for Telemedicine system



This is the most suitable medical camera for telemedicine system that enables remote-imaging treatment and prescription through network provided by qualified medical professionals.


ON

Convenient joystick

Convenient joystic with each directions can lead to freeze, save and zoom images conveniently.

Image management

- Captured images can be selectively saved onto internal memory (SD CARD) or USB.
- It can be connected to PC via USB port and manage saved images on main units more efficiently.
- · Various comparison and display. (1 to 4 frame)



* Zoom IN/OUT (X1.0 - X3.0)

• Full HD(1080i / 60 Frames)





Image Conversion

Image can be conversed in various ways



• 18W LED Lamp loaded

18W LED Lamp is brighter than 100W Halogen Lamp. 4800° K color temperature close to natural light makes it possible to realize clearer image than Halogen lamp.

Easy Connection with PC/Laptops

DCS pro can be easily connected to a computer via USB 2.0. Users can save digital data on a computer.



Video (Colposco	pe DCS-102	Pro
Colpobar Colpobar		Green filter	(California)
Video I	Rectosco	pe DCS-103	R Pro
Anoscope	<u> </u>	Air pump	
Endoso	opic Car	nera System	DCS-103E Pro
CCD Coup	() Der (Endo) Discope)	
Video (Dtoscope	Camera Sys	stem DCS-104T P
Tongue d		x30(<i>Optional</i>) x60	(Optional)
Video I	Dermasco	ope DCS-10	5 Pro
x35 x10)) 00 x450	Polarizing CAP	x 450
Video S	Scope for	r Optician D	CS-108 Pro
x30	x60	Contact lens test CA	P

Applications with various accessories

f = 18.5mm

OB / GYN Colposcopy • Easy diagnosis of Cervix with Colpobar. • Easy diagnosis of cervical erosion and CIN and CIS using built-in green filter. f = 25mm GS / Proctology Hemorrhoid Anoscope for Internal or External Hemorrhoids, Anal Fissure and Anal Fistula. f = 18.5mm General Surgery Compatible with various endoscopes • It is possible to connect rigid endoscopes to durable CCD coupler. f = 18.5mm ENT / PEDIATRY / I.M / F.M Diagnosis of ear drum and external auditory canal without inserting telescope deeply. • Optimized telescope diameter (3mm) for pediatric patients. f = 18.5mm • Tonsil, larynx, skin can be diagnosed by various accessories. Dermatology / Plastic Surgery Skin diagnosis Side illumination can reduce light reflection and diagnose pore, keratin clearly. High magnification by using various kinds of lens and caps. f = 18.5mm · Epidermis and pigmentation can be clearly diagnosed. Optician Iris diagnosis · Check on contact lens, conjunctivitis and Iris,